

PERFORMANCE STATEMENT

No: NTR01

(1)Product type identification code:

According to EN 14041:2004 AC:2006 AGT NATURA parquet all types and versions

(2)Purpose/purposes of use:

According to EN 14041:2004 floor covering for interior applications

(3)Manufacturer:

AGT Aaç San.Tic.A.S. Organize San. Bölgesi/ANTALYA-TURKEY

(4)Authorized representative:

(5)Assessment and Verification of Performance Invariance System / Systems:

According to EN 14041:2004 system 3

(6a)Harmonized standard:

EN 14041:2004



Notified body/bodies:



Notified body: Textilní zkušební ústav, s.p.

Václavská 6 658 41 Brno Czech Republic Notified Body No:1021

Protocol:1021-CPR-15/133

(7)Declared performance/s:

Characteristics	Classification	Harmonized Standard
<p>Reaction to fire according to EN 13501-1 Notified body: Textilní zkušební ústav, s.p. Václavská 6 658 41 Brno Czech Republic Notified Body No:1021 Protocol:1021-CPR-15/133</p>		<p>EN 14041:2004</p>
<p>Slip resistance according to EN 13893 Notified body: Textilní zkušební ústav, s.p. Václavská 6 658 41 Brno Czech Republic Notified Body No:1021 Protocol:1021-CPR-15/133</p>		<p>EN 14041:2004</p>

<p>Formaldehyde class according to EN 717-1 Notified body: Textilní zkušební ústav, s.p. Václavská 6 658 41 Brno Czech Republic Notified Body No:1021 Protocol:1021-CPR-15/133</p>		<p>EN 14041:2004</p>
<p>Quantitative determination of pentachlorophenol in wood – chromatographic method according to CEN/TR 14823:2203 Notified body: Textilní zkušební ústav, s.p. Václavská 6 658 41 Brno Czech Republic Notified Body No:1021 Protocol:1021-CPR-15/133</p>	 <p><0,1 mg/kg (ppm)</p>	<p>EN 14041:2004</p>

(8) Appropriate Technical Documentation and / or Special Technical Documentation:

Textilní zkušební ústav, s.p.

The conformity of the laminate flooring product described in item 1 to the product performance table specified in item 7 has been declared by the manufacturer defined in item 3 on 25.06.2015.

NAME: ONUR GÜVEN

TITLE: CHIEF EXECUTIVE OFFICER

SIGNATURE:



AGT PARQUET USER GUIDE AND CONFORMITY CERTIFICATE (AC3 and AC4) IN FLOOR HEATING SYSTEMS

Application:

AGT Parke, subject to the following conditions: It is suitable to be used in heated structures from the ground.

- The floor must be dry, clean, dust free and free from corn.
- Parquet can be laid on water-heated systems at the bottom. Since laminate parquet has high heat coefficient, it does not prevent heat transfer. It uniformly distributes the heat uniformly to the surface. Because of these properties, Laminate Flooring is a suitable material that significantly reduces heating costs compared to other flooring materials.
- If the surface to be applied is an electric floor heating system, the floor heating system is not suitable for laminate flooring even if it is in a slab or concrete layer.
- **Disposal of floor screed:** Floor screed; The laminate should be laid in accordance with the standards to be suitable for the application of parquet (the fluctuation on the surface should be max.4 mm in 1 meter)
- **Preheating:** Preheating is required before the installation process to bring the substrate to the proper level from the floor.
- **Concrete Floors:** Pre-heating should be done after leaving for 3 weeks according to the season conditions in newly completed structures.
- **Preheating Process;** Heating is carried out at 25 ° C for 12 hours on day 1, the heating at night is discontinued. 2nd day, Heating is carried out at 35 ° C for 12 hours, the heating at night is discontinued. On the 3rd day, heating is carried out for 12 hours at 45 ° C, the heating at night is terminated. Heating is carried out at 55 ° C on the fourth day, heating is continued without interruption at 55 ° C until the 16th day. On the 16th day, heating is carried out at 45 ° C for 12 hours, night heating is discontinued. On the 17th day, heating is carried out at 35 ° C for 12 hours, night heating is discontinued. On day 18, heating is carried out at 25 ° C for 12 hours and the system is left to rest.

Merkez | Head Office
Organize Sanayi Bölgesi
3. Kısım, 35. Caddesi 07190
Döşemealtı, Antalya, Turkey
Tel: +90 242 249 17 17
Fax: +90 242 249 17 27

İstanbul Ofis | İstanbul Office
Kısıklı Mah. Alemdağ Caddesi
No: 36 34692 Çamlıca,
İstanbul, Turkey
Tel: +90 216 344 82 48
Fax: +90 216 316 82 48
istanbul@agt.com.tr

agt.com.tr

 /agthinkwithus

The amount of moisture should be 18% maximum.

- **Anhydride Floors:** After finishing for 1 week according to seasonal conditions in new finished buildings, it should be heated up.
- **Preheating Process:** The process is done as done on concrete floors.
- **Test of the Soil Foundation:** 24 hours before the end of the heating process, 50x50 cm size polyethylene film is taped from the edges and adhered to the floor. After 24 hours there is no condensation in the film and the floor is ready for installation if the color of the floor is not different.
- **Kraft Paper Laying to Floor:** In under floor heating systems, the polyethylene mattress leads to heat loss. To remove this negative situation, flat or corrugated double layer 125gr / m2 craft paper should be laid instead of polyethylene mattress.
- Leave a space of 15 mm between the parquet and the wall, and the skirting boards should not fall into the parquet. That is, the floors should be laid on the floors.
- Laminate flooring in under floor heating systems is suitable up to 27 ° C. The surface temperature should not exceed 25°C.

We wish you to use it for good days, thank you for choosing AGT Parquet.

Merkez | Head Office
Organize Sanayi Bölgesi
3. Kısım, 35. Cadde 07190
Döşemealtı, Antalya, Turkey
Tel: +90 242 249 17 17
Fax: +90 242 249 17 27
agt@agt.com.tr

İstanbul Ofis | İstanbul Office
Kısıklı Mah. Alemdağ Caddesi
No: 36 34692 Çamlıca,
İstanbul, Turkey
Tel: +90 216 344 82 48
Fax: +90 216 316 82 48
istanbul@agt.com.tr

agt.com.tr

 /agthinkwithus

444 8 248



TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tanımı Description of the Mark
TSE veya/or  veya/or **T S E**

BELGE NUMARASI <i>REFERENCE NUMBER OF LICENCE</i>	024871-TSE-03/03
BELGENİN İLK VERİLİŞ TARİHİ <i>DATE OF FIRST ISSUE OF LICENCE</i>	24.07.2015
BELGENİN SON GEÇERLİLİK TARİHİ <i>LICENCE VALID UNTIL</i>	18.06.2019
BELGE SAHİBİ KURULUŞUN ADI <i>NAME OF THE LICENCE HOLDER</i>	AGT AĞAÇ SANAYİ VETİC.A.Ş.
BELGE SAHİBİ KURULUŞUN ADRESİ <i>ADRESS OF THE LICENCE HOLDER</i>	ORGANİZE SANAYİ BÖLGESİ 3.KISIM 35. CAD. NO:7 DÖŞEMEALTI ANTALYA/TÜRKİYE
ÜRETİM YERİ ADI <i>NAME OF THE MANUFACTURING PLACE</i>	AGT AĞAÇ SAN. VE TİC.LTD.ŞTİ.
ÜRETİM YERİ ADRESİ <i>ADRESS OF THE MANUFACTURING PLACE</i>	ORGANİZE SANAYİ BÖLGESİ 3.KISIM 35. CAD. NO:7 DÖŞEMEALTI ANTALYA / TÜRKİYE
İPTAL EDİLEN BELGE NUMARASI (Varsa) <i>INDICATION OF SUPERSEDED LICENCE (if any)</i>	024871-TSE-03/02
TESCİLLİ TİCARİ MARKASI <i>REGISTERED TRADE MARK</i>	AGT NATURA PARKE
İLGİLİ TÜRK STANDARDI <i>RELATED TURKISH STANDARD</i>	TS EN 13329 / Laminate floor coverings - Elements with a surface layer based on aminoplastic thermosetting resins - Specifications, requirements and test methods / 11.07.2016
BELGE KAPSAMI <i>SCOPE OF LICENCE</i>	INDOOR USE; ABRASION CLASS 23 (AC3) LAMİNATE FLOOR COVERINGS COMMERCIAL USE; ABRASION CLASS 31 (AC3) LAMİNATE FLOOR COVERINGS COMMERCIAL USE; ABRASION CLASS 32 (AC4) LAMİNATE FLOOR COVERINGS

16.07.2018

Belgelendirme Merkezi Başkanı Adına
NECİP FAZİL ÖĞÜT
ANTALYA BELGELENDİRME MÜDÜRÜ V.(V)

*Bu belge, belgelendirilen ürünün, üretim yerinin Enstitümüzün belirlediği şartları karşıladığını da gösterir.
*Bu belge hiç bir suretle tahrif edilemez, kısmen veya okunmasını zorlaştıracak şekilde çoğaltılamaz, kazıntı ve silinti yapılamaz.
*TSE ANTALYA BELGELENDİRME MÜDÜRLÜĞÜ * Adres: Gençlik Mah.İşıklar Cad.Falez Apt.No:59 ANTALYA * Tel: 0242-346 65 03 / 334 01 17* Faks: 0242-248 50 06
*TSE BELGELENDİRME MERKEZİ BAŞKANLIĞI; Adres: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Tel: 0 312 416 64 81 / 416 64 27, Faks: 0 312 416 66 17
e-posta : bmb@tse.org.tr , web : www.tse.org.tr

<https://evrakkontrol.tse.org.tr/BelgeDogrulama.aspx?p=vf2cjdxx> adresinden belgenin doğruluğunu ve geçerliliğini sorgulayınız.

